

Solar Wash Protect 50

Datasheet

Description

SOLAR WASH PROTECT 50 is a concentrated product which must be diluted in water to form the SWP solution.

This SWP solution is used to wash photovoltaic solar panels and its quick action makes it easy to clean all kinds of soiling. After the efficient washing it leaves on the solar panel a surface protection that will not allow the soiling to adhere so easily, protecting the solar panel from scratches and avoiding the fast decrease of solar panel power output due to soiling accumulation.

Dilution Specifications

1 kg of SWP 50 to 50 litres of water.

Applications

This product was developed to be used in washing of photovoltaic panels, facilitating its maintenance.

It can be used also to clean mirrors or lenses of Concentrated Solar Power systems (CSP).

Instructions of Use

1. Dilute/mix the SWP concentrated product with water in the right mixing ratio, to create ready-to-use SWP washing solution;
2. Use the SWP washing solution directly in the dirty solar panels;
3. Brush the entire surface of the modules in order to remove or loose the soiling present in the solar modules;
4. Rinse the panels with water to remove any dispersed soiling or excess of product left on the panels;
5. Let it dry on its own or remove the water with a Squeegee.

Important

NOTE: Apply or use the SWP washing Solution (after dilution) directly on the dirty solar panel;

NOTE2: After the scrub/brush step the rinsing with water final step is crucial for having the expected and good results.

Compatible
Applying/Cleaning
Equipments


Industrial sprays, Manual brush, Hoses, Rotative brushes, Robots, Tractors with brushes, etc.

Soiling and
Contaminants
Performance Table

Soiling	
Bird droppings	
Soil	
Sand	
Clay	
Carbon (e.g. exhaust gases)	
Coal Ash	
Pollen	
Bees' wax	
Decomposed organic material (leaves, flowers, bark, etc.)	
Tree sap / resin	
Salt residues	
Contaminants	
Grease	
Paint	use Paint Removal Agent
Aluminium Oxide	use Metal Oxides Removal Agent
Rust	use Metal Oxides Removal Agent
Cement dust and/or droppings	use Cement Removal Agent
Limestone dust	use Cement Removal Agent
Lichens	use Lichen Removal Agent
Fungi and moss	use Lichen Removal Agent
Bitumen	use Paint Removal Agent

Important Note:

The use of the correct equipment (e.g. brush) and the right amount of cleaning product are key to achieve the best results possible. Some types of soiling and contaminants may require a brush with stiffer bristles and/or a higher quantity of Solar Wash Protect per module.



Comments

Please follow the instructions in the safety data sheet for the safe handling of the product.

Properties

Aspect: Yellowish liquid;

Odor: Characteristic;

pH: 7 ± 1 ;

Density: 1,06g / cm³;

Solubility in water: Fully miscible.

Shelf life

Closed: 3 years

After opening: 6 months

After dilution: Use no later than 48 hours after dilution.

Packaging

Packaging of 500g, 5kg and 20 kg transparent drums and IBCs (1000kg bulk packaging containers).

