Technical Datasheet

SOLAR DRAINO



Solar Draino		
Nominal Size (Solar panel frame thickness)	Solar panel upper dimension	Standard packaging
40MM	11.5MM	500 / 1000pcs
35MM		
32MM		
30MM		

Advantages	Material Specification
Auto Remove Stagnant Water from solar panels	Engineering Plastic
Increase solar module power generation	
Improve the service life of solar panels.	
Easy installation. Automatically buckle onto the solar panel frame.	
Anti-aging material, high/low temperature resistance, effective long-term outdoor use	
Suitable for solar panel frame thickness: **30**mm, **32**mm, **35**mm,**40**mm	

Material	Average Life General	For Europe	For High UV index Regions	Weathering Effect	Properties
Engineering Plastic	10 to 20 years	upto 15 years	10 to 12 years	High weatherability	⊛ Non Flame Retardant ⊛ Good High and Low temprature resistance ⊛ High Chemical Resistance ⊛ Excellent UV Stability ⊛ Excellent Property Retention after Weathering ⊛ Heat Deflection Temp. : 102°C+

Email : info@solarcleanrobotics.ie
Website : www.solarprotectsolutions.ie
https://solarcleanrobotics.ie

Contact no. : +353 87 619 4077 (Ireland)
+44 739 360 3357 (U.K.)